Ser. No.: 10/643,606

Docket No. FA 1093 US NA

This listing of claims will replace all prior versions and listings of claims in the application:

## **Listing of Claims:**

- 1. (currently amended) A process for applying and curing a powder coating which comprises the steps of (1) applying the powder coating to a substrate; and (2) irradiation irradiating the applied powder coating with near infrared (NIR) radiation using NIR emitters, wherein the NIR radiation emitted from the NIR emitters has a wavelength ranging from about 250 to about 5500 nm; and 3) providing filters for the NIR emitters, wherein said filters are coated filters selected from borosilicate glass, silica glass, and vitreous ceramic; wherein said filters restrict the wavelength of the NIR radiation emitted from the emitters is restricted by filtration of the wavelength to a wavelength range of ranging from 250 to 3000 nm, wherein the restricted NIR radiation primarily has with a primary focus of the radiation in a wavelength range ranging from 750 to 1200 nm.
- (currently amended) The Process process according to claim 1 wherein said filters restrict the wavelength of the NIR radiation spectrum of the NIR radiation is restricted by filtration emitted from the emitters to a wavelength range ranging from ef 750 to 1800 nm.
- (currently amended) <u>The process</u> <u>Process</u> according to claim 1 wherein a combination is used of the NIR irradiation with a conventional heat source.
- 4. (currently amended) <u>The process</u> <u>Process</u> according to claim 3 wherein the conventional heat source is selected from the group consisting of infrared radiation, convection heat and gas infrared radiation emitters.
- 5. (canceled)

Ser. No.: 10/643,606

Docket No. FA 1093 US NA

6. (currently amended) The process Process according to claim 5 wherein the <u>coated</u> filters are coated on one or both sides with absorbent or reflective substances.

- 7. (currently amended) <u>The process</u> Process according to claim 1 wherein the powder coating is cured in a period from 0.5 to 60 seconds.
- 8. (currently amended) <u>The process Process</u> according to claim 1 wherein three-dimensional substrates are coated and cured.
- 9. (canceled)